

MODEL/TYP	SILA ZWARCIA	MANIPULATOR	SERWOMOTOR	ROZSTAW KOLUMN [BxH]	ŚREDNICA ŚLIMAKA	CISNIENIE WTRYSKU	GRAMATURA WTRYSKU	ILOŚĆ RDZENI	MIN. WYS. FORMY [A]	MAKS. WYS. FORMY [A+]
Model/type	Clamping force	Manipulator	Servomotor	Distance between tiebars	Screw diameter	Injection pressure	Injection weight	Number of roots	Min mold height	Max mold height
KM 40/220C1	40T	-	-	320x320 mm	30 mm	2500 barów	77 g	1	200 mm	350 mm
KM 50/220 C1	50T	-	-	320x320 mm	30 mm	2500 barów	77 g	1	300 mm	350 mm
KM 110/520 C2+	110T	-	-	470x460 mm	40 mm	2377 barów	198 g	1	300 mm	600 mm
KM 110/520 C2+	110T	-	-	470x460 mm	40 mm	2377 barów	198 g	1	300 mm	600 mm
KM 110/520 C2+	110T	-	-	470x460 mm	40 mm	2377 barów	198 g	1	300 mm	600 mm
KM 150/620 B1	150T	-	-	510x440 mm	50 mm	1638 barów	339 g	1	280 mm	600 mm
KM 150/1000 C1	150T	-	✓	510x500 mm	60 mm	1600 barów	566 g	2	300 mm	600 mm
FERROMATIK	275T	-	✓	630x630 mm	60 mm	1942 barów	681 g	2	300 mm	900 mm
HAITIAN	90T	✓	-	360x360 mm	36 mm	1730 barów	139 g	2	150 mm	380 mm
HAITIAN	200T	✓	-	530x530 mm	50 mm	1700 barów	375 g	2	200 mm	550 mm
HAITIAN	250T	✓	✓	580x580 mm	55 mm	1780 barów	519 g	2	220 mm	580 mm
HAITIAN	450T	✓	✓	810x810 mm	70 mm	1570 barów	1127 g	4	350 mm	850 mm
HAITIAN	550 T	✓	✓	910x810 mm	80 mm	2100 barów	1692 g	7	350 mm	1100 mm
HAITIAN	550 T	✓	✓	910x810 mm	80 mm	2100 barów	1692 g	7	350 mm	1100 mm
HAITIAN	550 T	✓	✓	910x810 mm	80 mm	2100 barów	1692 g	7	350 mm	1100 mm
HAITIAN	650T	✓	✓	1040x910 mm	85 mm	2100 barów	2272 g	4	400 mm	1250 mm
HAITIAN	750 T	✓	✓	1120x960 mm	100 mm	1800 barów	3359 g	8	450 mm	1250 mm
HAITIAN	900 T	✓	✓	1180x1000 mm	110 mm	1480 barów	4064 g	8	500 mm	1100 mm